



Door Hanger (Front)

Slurry Seal

Within the next 30 days, you will see construction crews and equipment preparing to treat and improve the roads in your neighborhood. This work will **depend on the weather**.

WHAT YOU NEED TO KNOW

Crews will be applying slurry seal, a mix of asphalt and stone that is spread over the road surface. This application is designed to extend the life of the pavement.

WHAT TO EXPECT

After the slurry seal has been applied, you may notice a small amount of stone remaining on the road. This is a normal and anticipated part of the project. Over the next 4 to 8 weeks, any excess stone should clear from the road surface from the movement of traffic, wind and weather conditions.

While resident will temporarily experience a different road texture, the product will cure to its final state several months after the work is concluded, and the difference will be far less evident.

If residents feel excess stone has not dissipated after 8 weeks, VDOT can assess whether additional roadway sweeping is necessary.

HOW TO PREPARE

When work begins, please avoid parking your vehicles on the street. Construction crews will place “No Parking” signs on the affected streets a minimum of 3 business days before work begins, notifying residents of the specific days parking will be prohibited. Please remove other obstructions from the road, such as basketball hoops or garbage cans.

RESOURCES

For more information about this process, please visit www.virginiadot.org/slurryseal.

To contact us, call VDOT’s Customer Service Center at 1-800-FOR-ROAD (800-367-7623) or email customerservice@VDOT.Virginia.Gov.

Scan this QR code using a smartphone to view VDOT information on asphalt.



NO PARKING

STREET PAVING

Project # _____

DATES: _____ --- _____

Time: _____ --- _____



FOR INFORMATION CALL: _____

CARS TOWED